

Casing	Colour				Almond white
Dimensions	Unit	Height		mm	490
		Width		mm	1050
		Depth		mm	200
Fan	Air Flow Rate	Cooling	High	m ³ /min	12.00
			Medium	m ³ /min	10.70
			Low	m ³ /min	9.30
			Silent Operation	m ³ /min	8.3
		Heating	High	m ³ /min	12.80
			Medium	m ³ /min	10.60
			Low	m ³ /min	8.40
			Silent Operation	m ³ /min	7.5
Sound level	Cooling	Sound Power	High	dBA	64.0
			Sound Pressure	High	dBA
		Sound Pressure	Medium	dBA	45.0
			Low	dBA	41.0
			Silent Operation	dBA	39.0
	Heating	Sound Power	High	dBA	63.0
			Sound Pressure	High	dBA
		Sound Pressure	Medium	dBA	42.0
			Low	dBA	37.0
			Silent Operation	dBA	34.0
Refrigerant	Type				R-410A
Power Supply	Phase				1~
	Frequency			Hz	50/60
	Voltage			V	220-240/220-230

Casing	Colour			Almond white	
Dimensions	Unit	Height	mm	490	
		Width	mm	1050	
		Depth	mm	200	
Fan	Air Flow Rate	Cooling	High	m ³ /min	8.60
			Medium	m ³ /min	7.60
			Low	m ³ /min	6.60
			Silent Operation	m ³ /min	5.6
		Heating	High	m ³ /min	9.80
			Medium	m ³ /min	8.90
			Low	m ³ /min	8.00
			Silent Operation	m ³ /min	7.2
Sound level	Cooling	Sound Power	High	dBA	54.0
			Sound Pressure	High	dBA
		Sound Pressure	Medium	dBA	35.0
			Low	dBA	32.0
			Silent Operation	dBA	29.0
	Heating	Sound Pressure	High	dBA	39.0
			Medium	dBA	36.0
			Low	dBA	33.0
Silent Operation			dBA	30.0	
Refrigerant	Type			R-410A	
Power Supply	Phase			1~	
	Frequency		Hz	50/60	
	Voltage		V	220-240/220-230	

Casing	Colour				Almond white
Dimensions	Unit	Height		mm	490
		Width		mm	1050
		Depth		mm	200
Fan	Air Flow Rate	Cooling	High	m ³ /min	7.60
			Medium	m ³ /min	6.80
			Low	m ³ /min	6.00
			Silent Operation	m ³ /min	5.2
		Heating	High	m ³ /min	9.20
			Medium	m ³ /min	8.30
			Low	m ³ /min	7.40
			Silent Operation	m ³ /min	6.6
Sound level	Cooling	Sound Power	High	dBA	53.0
			Sound Pressure	High	dBA
		Sound Pressure	Medium	dBA	34.0
			Low	dBA	31.0
			Silent Operation	dBA	28.0
	Heating	Sound Pressure	High	dBA	37.0
			Medium	dBA	34.0
			Low	dBA	31.0
Silent Operation			dBA	29.0	
Refrigerant	Type				R-410A
Power Supply	Phase				1~
	Frequency			Hz	50/60
	Voltage			V	220-240/220-230

Casing	Colour				Almond white
Dimensions	Unit	Height		mm	490
		Width		mm	1050
		Depth		mm	200
Fan	Air Flow Rate	Cooling	High	m ³ /min	11.40
			Medium	m ³ /min	10.00
			Low	m ³ /min	8.50
			Silent Operation	m ³ /min	7.6
		Heating	High	m ³ /min	12.1
			Medium	m ³ /min	9.8
			Low	m ³ /min	7.5
			Silent Operation	m ³ /min	6.8
Sound level	Cooling	Sound Power	High	dBA	63.0
			Sound Pressure	High	dBA
		Sound Pressure	Medium	dBA	43.0
			Low	dBA	39.0
			Silent Operation	dBA	36.0
	Heating	Sound Power	High	dBA	62.0
			Sound Pressure	High	dBA
		Sound Pressure	Medium	dBA	41.0
			Low	dBA	35.0
			Silent Operation	dBA	33.0
Refrigerant	Type				R-410A
Power Supply	Phase				1~
	Frequency			Hz	50/60
	Voltage			V	220-240/220-230