

Ururu streamer technology air purifier

MCK70YV



Humidification



Flash Streamer

Humidification and air purification in one

- › Air purification for large spaces such as residential and light commercial applications
- › Pure air thanks to Daikin 'Catch and Clean' approach in decomposing harmful substances
- › High performance electrostatic HEPA filter with no need to change for 10 years
- › One of the most silent Air Purifier range on the European market




MCK70YV



Price with 20%VAT.				BGN	1728,-
					Floor standing type
Applicable room area				m²	48 (1) / 96 (2)
CADR				m³/h	375 (3)
Weight	Unit			kg	12.5
Dimensions				mm	461 / 695 / 347
Casing	Colour				White (N9.0)
Fan	Type				Multi Blade Fan (Sirocco fan)
	Air flow rate	Air purifying operation	Silent/Low/Medium/Turbo	m³/h	60 /132 /210 /420
		Humidifying operation	Silent/Low/Medium/Turbo	m³/h	102 /132 /210 /420
Sound pressure level (5)	Air purifying operation	Silent/Low/Medium/Turbo		dBa	18 /27 /37 /54
	Humidifying operation	Silent/Low/Medium/Turbo		dBa	23 /27 /37 /54
Humidifying operation	Power input	Silent/L/M/Turbo		kW	0.011 /0.012 /0.018 /0.068
	Humidification(4)	Turbo		ml/h	650
	Water tank capacity			l	3.6
Air purifying operation	Power input	Silent/L/M/Turbo		kW	0.008 /0.010 /0.016 /0.066
Deodorizing method					Flash streamer + Deodorizing catalyst
Dust collecting method					Electrostatic HEPA filter (6) (7)
Air filter	Type				Polyethylene terephthalate net
Sign	Item	01		Dust sensor lamp: 3 stages / / PM 2.5 sensor lamp: 3 stages / Odour sensor lamp: 3 stages / / Humidity monitor : 20% - 90% / Humildity setting: Low/Standard/High / Airflow rate: Quiet/Low/Standard/Turbo / AUTO FAN mode / Econo mode / Anti-pollen mode / MOIST mode / CIRCULATION mode / Water supply lamp / Streamer lamp / Humidifier ON/OFF lamp / Sleep mode / Child proof lock lamp / AUTO operation lamp	
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/60/220-240/220-230
Type					Humidifying air purifier

(1) The coverage area is appropriate for operating the unit of maximum fan speed(HH). Coverage area indicates the space where a certain amount of dust particles can be removed in 30 minutes. |
(2) Converted to NRCC standards from test values in accordance with JEM1467. |
(3) Converted to CADR standards from test values in accordance with JEM1467. |
(4) Humidification amount changes in accordance with indoor and outdoor temperature and humidity. Measurement condition: 20°C in temperature, 30% in humidity. |
(5)Operating sound levels are the average of values measured at 1m away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) |
(6) Electrostatic HEPA filter and humidifying filters are attached in the unit. |
(7) Requirements according to JEM1467.



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

03/2022

