

Daikin Altherma 3 R MT  
The Quintessence of heat pump  
**Product catalogue**



**Mid temperature air-to-water heat pump,  
optimized for boiler replacement**

Heating, cooling and domestic hot water





# Table of contents

<b>The ideal boiler replacement .....</b>	<b>4</b>
<b>Daikin Altherma 3 R MT .....</b>	<b>6</b>
The Quintessence of heat pump .....	6
Innovation at the heart of our concerns.....	8
One solution, multiple combinations .....	10
Get the best comfort with the best functionalities .....	11
Floor standing unit with integrated tank .....	12
Floor standing unit with integrated ECH <sub>2</sub> O tank.....	20
Wall mounted unit .....	26
<b>Thermal stores and tanks .....</b>	<b>32</b>
Thermal stores .....	34
Domestic hot water tanks .....	35
<b>Heat pump convectors .....</b>	<b>36</b>
Daikin Altherma HPC floor standing .....	36
Daikin Altherma HPC wall mounted .....	38
Daikin Altherma HPC concealed .....	39
<b>Controls .....</b>	<b>42</b>
Onecta App .....	42
Madoka .....	44
<b>Stand By Me .....</b>	<b>46</b>
<b>Combination table and options .....</b>	<b>50</b>



# The ideal boiler replacement gets extended

## Ideal to replace gas boilers


Houses built in the 90s often need a refurbishment to still look up-to-date.

In a renovation project, this is also important to consider changing your initial heating system.

Daikin Altherma 3 R MT come as a perfect replacement in such houses, where a leaving water temperature of 65 °C is sufficient. Easy to install, you can even leave the recent radiators installed!

## Suitable for medium sized new buildings

With a capacity range going from 8 to 12 class, Daikin Altherma 3 R MT also fit in medium sized new buildings.



## Daikin Altherma 3 R MT offers multiple possibilities to adapt to your customers needs

- ✓ A leaving water temperature up to 65 °C makes it **a suitable choice for refurbishments**
- ✓ **Best seasonal efficiencies** providing the highest savings on running costs
- ✓ Perfect fit for **new buildings**, as well as for low energy houses



### Refrigerant split version

Daikin Altherma 3 range presents a new addition to the family – refrigerant split version for medium temperature heat pump.

Daikin Altherma 3 R MT relies on a compressor and a refrigerant to transfer the energy from the air to the water. The Refrigerant split unit provides cooling next to heating and domestic hot water.

### Better fit with hydrosplit versions ?

The Daikin Altherma 3 solutions for replacement do come also in hydrosplit versions, 3 H MT and 3 H HT. More information can be found here:



# The Quintessence of heat pump

meeting modern society's expectations



## Made in Europe, for Europe

European weather can be tough sometimes. That's why we designed the Daikin Altherma 3 R MT.

Heating capacities are also maintained high by low ambient temperature thanks to genuine Daikin technology.

As the market leader, Daikin is always striving to make the most reliable and efficient heat pumps possible. Daikin developed the Bluevolution technology to achieve higher and greener performance. This technology is now part of all our heat pumps. Its single fan reduces the noise level and its black front grille makes the unit fit into any environment.

All these dedicated components were developed in-house to make the quintessence of heat pump unique.

**Superior performance, renewable energy use, design and acoustic comfort.**  
**This is what the Quintessence of heat pump is all about.**

## BLUEvolution

The Bluevolution technology combines a specifically developed compressor and the R-32 refrigerant. Daikin is one of the pioneers in the world to launch heat pumps equipped with R-32. With a lower Global Warming Potential (GWP), the R-32 is equivalent in power to standard refrigerants, but achieves higher energy efficiency and lower CO<sub>2</sub> emissions.


Easy to recover and re-use, R-32 is the perfect solution to attain the new European CO<sub>2</sub> emission targets.

**R-32**

## Timeless design and space-saving installation

Aside from the acoustic comfort, design is a decisive point nowadays. Specific attention was paid to making the outdoor unit blend in with your home.

The black front grille stretches horizontally making the fan inside invisible. The mat grey casing reflects the colour of the wall behind for more discretion. When first launched, this unit received two design awards in 2019. This award winning design has been continued in the new models.







## Silence rhymes with comfort

The Quintessence of heat pump has been designed to reduce its acoustic level and meet the expectations of today's society.

In standard sound mode, the unit produces a sound pressure of 38 dBA at 3 metres, so somewhere between birds chirping and the inside of a library.

The unit also offers greater flexibility by having a low sound mode that reduces the sound pressure at 3 metres to 35 dBA, representing a real reduction of half the sound level!



## The acoustic level can be evaluated in two ways

- › The **sound power** is generated by the unit itself, independently of distance and environment
- › The **sound pressure** is the sound perceived at a certain distance. The sound pressure is usually calculated at between 1 and 5 metres from the unit.

\* Erp sound power: Daikin Altherma 3 R MT: 56 dBA

# Innovation At the heart of our concerns

The Daikin Altherma 3 R MT is at top of low sound and heating performances thanks to dedicated developments. Several major components are designed to make this product reach the excellence such as a double injection compressor and a single fan even for large capacity units as well as a brand-new casing.

## A contemporary design casing

The black front grille made of horizontal lines is hiding the fan from view, reducing the perception of the sound produced by the unit.

The light grey casing is slightly reflecting the environment where the unit is installed, helping it to blend in in any decor.

This unique design already got design awards.



**reddot design award**  
winner 2019

## A single fan for all capacities

The single fan is slightly larger, replacing the usual double fan for high capacity units (classes 8-10-12).

The shape of the fan has also been reviewed to reduce the contact surface with air therefore lower the sound level by improving the air circulation.






## Compressor insulation and anti-vibration

To reduce the compressor sound power, several actions were taken in terms of absorption and insulation.

First, the compressor is surrounded by a 3-layer insulation made of air, insulation material and a metal box.

Regarding the absorption, the unit benefits from a double sound reduction by using rubber pads between the bottom plate and the vibration plate under the compressor.



## New double injection compressor

To make this product unique, Daikin Europe cooperated with Daikin Japan to develop top notch components. Daikin Altherma 3 R MT is available in classes 8-10-12 delivers up to 65 °C leaving water temperature.

## Impressive performance

In line with our other heat pump models optimized for replacement, the Daikin Altherma 3 R MT reaches the best performances illustrated in the energy labels:



# One solution, multiple combinations

The Quintessence range can be combined with three different indoor units to connect to the outdoor unit, offering specific features to ensure heating, cooling and domestic hot water in your home.

## Outdoor unit

The outdoor unit is available in 3 classes for 3 R MT: 8-10-12 kW



## Integrated DHW stainless steel tank model

This model is a compact unit with a small footprint of 595x625 mm. The unit is equipped with a tank of 180 or 230 L to answer your domestic hot water demand. Optionally, you can choose the cooling or the bizon functions.




## Integrated ECH<sub>2</sub>O DHW tank model

The ECH<sub>2</sub>O unit is equipped with a thermal DHW tank of 300 or 500 L that can be connected to thermal solar panels. Optionally, you can choose the cooling function.



## Wall mounted model

This model is the most compact unit but needs to be with a separate tank to deliver domestic hot water. Optionally, you can choose the cooling function.



See exact dimensions per model in the specification tables (p22-29).

# Get the best comfort

## with the best functionalities


Choose from the Daikin "Three Pluses" the functionality that best fits your customer's needs. The indoor units come in 3 possible versions: heating only, reversible and bizone, giving you the opportunity to tailor your Daikin heating system.

### + Heating only model

The heating only model is standard in the Daikin product range and is available for all three indoor units. This means that your heating system provides space heating and domestic hot water.

### + Reversible model

If cooling is needed, all three indoors have dedicated reversible models. Reversible means that the system can invert its way of working and provide cooling instead of heating. The cooling function requires a underfloor piping system or heat pump convectors.



### + Bizone model

Only the DHW stainless steel tank model has a dedicated bizone model: you can choose two independent zones with different emitters that need a different temperature level in different rooms (example: underfloor system in the living room and radiators in the bedroom upstairs).

The 2 zones can also be managed independently: deactivate heating on the first floor during the day in order to reduce over consumption.

\* Daikin Altherma 3 R MT produces a LWT up to 65 °C (08-10-12 classes).

## Floor standing unit with integrated tank

### Why choose Daikin floor standing unit with integrated domestic hot water tank?


The Daikin Altherma 3 floor standing unit is the ideal system **to deliver heating, domestic hot water and cooling** for renovation or large new built.

#### All in one system to save installation space and time

- › A combined stainless steel domestic hot water tank of 180 or 230 L and heatpump ensures a faster installation compared to traditional systems.
- › Inclusion of all hydraulic components means no third party components are required.
- › PCB board and hydraulic components are located in the front for easy access
- › Small installation footprint of 595 x 625 mm
- › Integrated back-up heater choice of 6, 9 kW models are available
- › Dedicated bi-zone models allowing temperature monitoring for 2 zones.

#### Heating and cooling

#### Domestic hot water



#### Underfloor heating



# All-in one design

## Reduces the installation footprint and height


Compared to the traditional split version for a wall mounted indoor unit and a separate domestic hot water tank, the integrated indoor unit greatly reduces the installation space required.

With a small footprint of 595 x 625 mm, the integrated indoor unit has a similar footprint when compared to other household appliances.

For installation projects, almost no side clearance is necessary as the piping is located at the top of the unit.

With an installation height of 1,65 m for an 180 L tank and 1,85 m for a 230 L tank, the required installation height is less than 2m.

The compactness of the integrated indoor unit is emphasised by its sleek design and modern look, easy blending in with other household appliances.



## Advanced user interface



### The Daikin Eye

The intuitive Daikin eye shows you in real time the status of your system.

Blue is perfect! Should the eye turn red, an error has occurred.

### Quick to configure

Log in and you'll be able to completely configure the unit via the new interface in less than 10 steps. You can even check if the unit is ready for use by running test cycles!

### Easy operation

Work super-fast with the new interface. It's super easy to use with just a few buttons and 2 navigational knobs.

### Beautiful design

The interface was especially designed to be very intuitive. The high contrasted colour screen delivers stunning and practical visuals that really help you as installer or service engineer.

## Integrated indoor unit





# Daikin Altherma 3 R MT

Floor standing air to water heat pump for **heating and hot water**, ideal for low energy houses

- › A combined stainless steel domestic hot water tank of 180 or 230L and heat pump for easy installation
- › Energy efficient heating only system based on air to water heat pump technology
- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Inclusion of all hydraulic components means no third party components are required
- › The unit's sleek design blends in with other household appliances



Efficiency data				ELVH + ERRA	12S18E6V/9W + 08EW1	12S23E6V/9W + 08EW1	12S18E6V/9W + 10EW1	12S23E6V/9W + 10EW1	12S18E6V/9W + 12EW1	12S23E6V/9W + 12EW1	
	Space heating	Average climate water outlet 55 °C	General	SCOP ηs (Seasonal space heating efficiency) Seasonal space heating eff. class	%	3,42		3,43		3,53	
						134				138	
						A++					
		Average climate water outlet 35 °C	General	SCOP ηs (Seasonal space heating efficiency) Seasonal space heating eff. class	%	4,81		4,84			
						190		191			
	Domestic hot water heating	General	Declared load profile			A+++ L					
		Average climate	COP	dh <sub>w</sub>		2,8	3,05	2,8	3,05	2,8	3,05
			η <sub>wh</sub> (water heating efficiency)	%		120	130	120	130	120	130
			Water heating energy efficiency class			A+					
Indoor Unit				ELVH	12S18E6V/9W	12S23E6V/9W	12S18E6V/9W	12S23E6V/9W	12S18E6V/9W	12S23E6V/9W	
Casing	Colour				White + Black						
	Material				Precoated sheet metal						
Dimensions	Unit	HeightxWidthxDepth	mm		1,655 x 595 x 634	1,855 x 595 x 634	1,655 x 595 x 634	1,855 x 595 x 634	1,655 x 595 x 634	1,855 x 595 x 634	
Weight	Unit				kg	120	129	120	129	120	129
Tank	Water volume				l	180	230	180	230	180	230
	Maximum water temperature				°C	70					
	Maximum water pressure				bar	10					
	Corrosion protection					Pickling					
Operation range	Heating	Ambient	Min.~Max.	°C	-25 ~ 25						
		Water side	Min.~Max.	°C	15 ~ 65						
	Domestic hot water	Ambient	Min.~Max.	°C	-25 ~ 35						
		Water side	Min.~Max.	°C	25 ~ 62						
Sound power level	Nom.				dBA	44					
Sound pressure level	Nom.				dBA	30					
Outdoor Unit				ERRA	08EW1	10EW1	12EW1				
Dimensions	Unit	HeightxWidthxDepth	mm		1,003 x 1,270 x 533						
Weight	Unit				kg	107					
Compressor	Quantity					1					
	Type					Hermetically sealed swing compressor					
Operation range	Heating	Min.~Max.		°CDB	-25 ~ 25						
	Cooling	Min.~Max.		°CDB	10 ~ 43						
	Domestic hot water	Min.~Max.		°CDB	-25 ~ 35						
Refrigerant	Type					R-32					
	GWP					675					
	Charge				kg	3,25					
	Charge				TCO <sub>2</sub> /Eq	2,19					
	Control					Expansion valve					
LW(A) Sound power level (according to EN14825)					56						
Sound pressure level (at 1 meter)					41,1						
Power supply	Name/Phase/Frequency/Voltage			Hz/V	W1/3~/50 /400						
Current	Recommended fuses			A	16						



This product contains fluorinated greenhouse gases.

# Daikin Altherma 3 R MT

Floor standing air to water heat pump for **heating and hot water**, ideal for low energy houses

- › A combined stainless steel domestic hot water tank of 180 or 230L and heat pump for easy installation
- › Energy efficient heating only system based on air to water heat pump technology
- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Inclusion of all hydraulic components means no third party components are required
- › The unit's sleek design blends in with other household appliances




Efficiency data				ELVH + ERRA	12S18E6V/9W + 08EV3	12S23E6V/9W + 08EV3	12S18E6V/9W + 10EV3	12S23E6V/9W + 10EV3	12S18E6V/9W + 12EV3	12S23E6V/9W + 12EV3	
	Space heating	Average climate water outlet 55 °C	General	SCOP	3,34			3,44			
				ηs (Seasonal space heating efficiency)	130	131		135			
		Seasonal space heating eff. class	A++								
	Average climate water outlet 35 °C	General	SCOP	4,69			4,71				
			ηs (Seasonal space heating efficiency)	184	186						
		Seasonal space heating eff. class	A+++								
	Domestic hot water heating	Average climate	Declared load profile		L						
			COP	dhw	2,72	2,96	2,72	2,96	2,72	2,96	
		ηwh (water heating efficiency)	%	117	126	117	126	117	126		
		Water heating energy efficiency class	A+								
	Indoor Unit					ELVH	12S18E6V/9W	12S23E6V/9W	12S18E6V/9W	12S23E6V/9W	12S18E6V/9W
Casing	Colour				White + Black						
	Material				Precoated sheet metal						
Dimensions	Unit	HeightxWidthxDepth mm			1,655 x 595 x 634	1,855 x 595 x 634	1,655 x 595 x 634	1,855 x 595 x 634	1,655 x 595 x 634	1,855 x 595 x 634	
Weight	Unit	kg			120	129	120	129	120	129	
Tank	Water volume l			180	230	180	230	180	230		
	Maximum water temperature °C			70							
	Maximum water pressure bar			10							
	Corrosion protection			Pickling							
Operation range	Heating	Ambient	Min.~Max.	°C	-25 ~ 25						
		Water side	Min.~Max.	°C	15 ~ 65						
	Domestic hot water	Ambient	Min.~Max.	°C	-25 ~ 35						
		Water side	Min.~Max.	°C	25 ~ 62						
Sound power level	Nom.	dBA			44						
Sound pressure level	Nom.	dBA			30						
Outdoor Unit					ERRA	08EV3	10EV3		12EV3		
Dimensions	Unit	HeightxWidthxDepth mm			1,003 x 1,270 x 533						
Weight	Unit	kg			107						
Compressor	Quantity			1							
	Type			Hermetically sealed swing compressor							
Operation range	Heating	Min.~Max.		°CDB	-25 ~ 25						
	Cooling	Min.~Max.		°CDB	10 ~ 43						
	Domestic hot water	Min.~Max.		°CDB	-25 ~ 35						
Refrigerant	Type				R-32						
	GWP				675						
	Charge	kg			3,25						
	Charge	TCO <sub>2</sub> /Eq			2,19						
	Control				Expansion valve						
LW(A) Sound power level (according to EN14825)					54						
Sound pressure level Nom. (at 1 meter)					40,6						
Power supply	Name/Phase/Frequency/Voltage			Hz/V	V3/1~/50 /230						
Current	Recommended fuses			A	32						



This product contains fluorinated greenhouse gases.

# Daikin Altherma 3 R MT F

Floor standing air to water heat pump for **heating**, **cooling** and **hot water**, ideal for low energy houses

- › A combined stainless steel domestic hot water tank of 180 or 230L and heat pump for easy installation
- › For hot water, heating and cooling
- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Inclusion of all hydraulic components means no third party components are required
- › The unit's sleek design blends in with other household appliances



Efficiency data				ELVX + ERRA	12S18E6V/9W + 08EW1	12S23E6V/9W + 08EW1	12S18E6V/9W + 10EW1	12S23E6V/9W + 10EW1	12S18E6V/9W + 12EW1	12S23E6V/9W + 12EW1	
	Average climate water outlet 55 °C	General	SCOP	%	3,47		3,48		3,58		
			ηs (Seasonal space heating efficiency)	%	136				140		
			Seasonal space heating eff. class		A++						
	Average climate water outlet 35 °C	General	SCOP	%	4,95		4,98				
			ηs (Seasonal space heating efficiency)	%	195		196				
	Average climate	General	Seasonal space heating eff. class		A+++						
			Declared load profile		L						
			COP	dhw	2,8	3,05	2,8	3,05	2,8	3,05	
			ηwh (water heating efficiency)	%	120	130	120	130	120	130	
				Water heating energy efficiency class		A+					
Indoor Unit				ELVX	12S18E6V/9W	12S23E6V/9W	12S18E6V/9W	12S23E6V/9W	12S18E6V/9W	12S23E6V/9W	
Casing	Colour				White + Black						
	Material				Precoated sheet metal						
Dimensions	Unit	HeightxWidthxDepth mm			1,655 x 595 x 634	1,855 x 595 x 634	1,655 x 595 x 634	1,855 x 595 x 634	1,655 x 595 x 634	1,855 x 595 x 634	
Weight	Unit				kg	120	129	120	129	120	129
Tank	Water volume				l	180	230	180	230	180	230
	Maximum water temperature				°C	70					
	Maximum water pressure				bar	10					
	Corrosion protection					Pickling					
Operation range	Heating	Ambient	Min.~Max.	°C	-25 ~ 25						
		Water side	Min.~Max.	°C	15 ~ 65						
	Domestic hot water	Ambient	Min.~Max.	°C	-25 ~ 35						
		Water side	Min.~Max.	°C	25 ~ 62						
Sound power level	Nom.				dBA	44					
Sound pressure level	Nom.				dBA	30					
Outdoor Unit				ERRA	08EW1		10EW1		12EW1		
Dimensions	Unit	HeightxWidthxDepth mm			1,003 x 1,270 x 533						
Weight	Unit				kg	107					
Compressor	Quantity				1						
	Type				Hermetically sealed swing compressor						
Operation range	Heating		Min.~Max.	°CDB	-25 ~ 25						
	Cooling		Min.~Max.	°CDB	10 ~ 43						
	Domestic hot water		Min.~Max.	°CDB	-25 ~ 35						
Refrigerant	Type				R-32						
	GWP				675						
	Charge				kg	3,25					
	Charge				TCO <sub>Eq</sub>	2,19					
	Control				Expansion valve						
LW(A) Sound power level (according to EN14825)					56						
Sound pressure level (at 1 meter)					41,1						
Power supply	Name/Phase/Frequency/Voltage			Hz/V	W1/3~/50 /400						
Current	Recommended fuses			A	16						

This product contains fluorinated greenhouse gases.





# Daikin Altherma 3 R MT F

Floor standing air to water heat pump for **heating**, **cooling** and **hot water**, ideal for low energy houses

- › A combined stainless steel domestic hot water tank of 180 or 230L and heat pump for easy installation
- › For hot water, heating and cooling
- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Inclusion of all hydraulic components means no third party components are required
- › The unit's sleek design blends in with other household appliances



Efficiency data				ELVX + ERRA	12S18E6V/9W + 08EV3	12S23E6V/9W + 08EV3	12S18E6V/9W + 10EV3	12S23E6V/9W + 10EV3	12S18E6V/9W + 12EV3	12S23E6V/9W + 12EV3		
	Space heating	Average climate water outlet 55 °C	General	SCOP ηs (Seasonal space heating efficiency) Seasonal space heating eff. class	%	3,37		3,38		3,47		
						132				136		
						A++						
		Average climate water outlet 35 °C	General	SCOP ηs (Seasonal space heating efficiency) Seasonal space heating eff. class	%	4,79		4,82				
						188		190				
	Domestic hot water heating	General	Declared load profile			A+++ L						
		Average climate	COP	dhw	%	2,72	2,96	2,72	2,96	2,72	2,96	
			ηwh (water heating efficiency)	%		117	126	117	126	117	126	
			Water heating energy efficiency class			A+						
Indoor Unit					ELVX	12S18E6V/9W	12S23E6V/9W	12S18E6V/9W	12S23E6V/9W	12S18E6V/9W	12S23E6V/9W	
Casing	Colour					White + Black						
	Material					Precoated sheet metal						
Dimensions	Unit	HeightxWidthxDepth		mm		1,655 x 595 x 634	1,855 x 595 x 634	1,655 x 595 x 634	1,855 x 595 x 634	1,655 x 595 x 634	1,855 x 595 x 634	
Weight	Unit					kg	120	129	120	129	120	129
Tank	Water volume					l	180	230	180	230	180	230
	Maximum water temperature					°C	70					
	Maximum water pressure					bar	10					
	Corrosion protection						Pickling					
Operation range	Heating	Ambient	Min.~Max.		°C	-25 ~25						
		Water side	Min.~Max.		°C	15 ~65						
	Domestic hot water	Ambient	Min.~Max.		°C	-25 ~35						
		Water side	Min.~Max.		°C	25 ~62						
Sound power level	Nom.					dBA	44					
Sound pressure level	Nom.					dBA	30					
Outdoor Unit					ERRA	08EV3	10EV3	12EV3				
Dimensions	Unit	HeightxWidthxDepth		mm		1,003 x 1,270 x 533						
Weight	Unit					kg	107					
Compressor	Quantity						1					
	Type						Hermetically sealed swing compressor					
Operation range	Heating	Min.~Max.		°CDB		-25 ~ 25						
	Cooling	Min.~Max.		°CDB		10 ~ 43						
	Domestic hot water	Min.~Max.		°CDB		-25 ~ 35						
Refrigerant	Type						R-32					
	GWP						675					
	Charge					kg	3,25					
	Charge					TCO <sub>Eq</sub>	2,19					
	Control						Expansion valve					
LW(A) Sound power level (according to EN14825)						54						
Sound pressure level (at 1 meter)						40,6						
Power supply	Name/Phase/Frequency/Voltage				Hz/V	V3/1~/50 /230						
Current	Recommended fuses				A	32						



This product contains fluorinated greenhouse gases.

# Daikin Altherma 3 R MT F

Floor standing unit integrated with different temperature zones management

- › A combined stainless steel domestic hot water tank of 180 or 230L and heat pump for easy installation
- › Bi-zone allows temperature monitoring for 2 zones. Connect underfloor heating to radiators to optimise efficiency
- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Inclusion of all hydraulic components means no third party components are required
- › The unit's sleek design blends in with other household appliances



Efficiency data				ELVZ + ERRA	12S18E6V/9W + 08EW1	12S23E6V/9W + 08EW1	12S18E6V/9W + 10EW1	12S23E6V/9W + 10EW1	12S18E6V/9W + 12EW1	12S23E6V/9W + 12EW1	
	Space heating	Average climate water outlet 55 °C	General	SCOP	3,42		3,43		3,58		
				ηs (Seasonal space heating efficiency)	134		134		138		
				Seasonal space heating eff. class	A++						
	Average climate water outlet 35 °C	General	SCOP	4,81		4,84					
			ηs (Seasonal space heating efficiency)	190		191					
	Domestic hot water heating	Average climate		Seasonal space heating eff. class	A+++						
					L						
			General	Declared load profile							
			COP	dhw	2,8	3,05	2,8	3,05	2,8	3,05	
			ηwh (water heating efficiency)	%	120	130	120	130	120	130	
			Water heating energy efficiency class	A+							
Indoor Unit				ELVZ	12S18E6V/9W	12S23E6V/9W	12S18E6V/9W	12S23E6V/9W	12S18E6V/9W	12S23E6V/9W	
Casing	Colour				White + Black						
	Material				Precoated sheet metal						
Dimensions	Unit	HeightxWidthxDepth	mm		1,655 x 595 x 634	1,855 x 595 x 634	1,655 x 595 x 634	1,855 x 595 x 634	1,655 x 595 x 634	1,855 x 595 x 634	
Weight	Unit		kg		133	141	133	141	133	141	
Tank	Water volume		l		180	230	180	230	180	230	
	Maximum water temperature		°C		70						
	Maximum water pressure		bar		10						
	Corrosion protection				Pickling						
Operation range	Heating	Ambient	Min.~Max.	°C	-25 ~ 25						
		Water side	Min.~Max.	°C	15 ~ 65						
	Domestic hot water	Ambient	Min.~Max.	°C	-25 ~ 35						
		Water side	Min.~Max.	°C	25 ~ 62						
Sound power level	Nom.			dBA	44						
Sound pressure level	Nom.			dBA	30						
Outdoor Unit				ERRA	08EW1	08EW1	10EW1	10EW1	12EW1	12EW1	
Dimensions	Unit	HeightxWidthxDepth	mm		1,003 x 1,270 x 533						
Weight	Unit		kg		107						
Compressor	Quantity				1						
	Type				Hermetically sealed swing compressor						
Operation range	Heating	Min.~Max.	°CDB		-25 ~ 25						
	Cooling	Min.~Max.	°CDB		10 ~ 43						
	Domestic hot water	Min.~Max.	°CDB		-25 ~ 35						
Refrigerant	Type				R-32						
	GWP				675						
	Charge		kg		3,25						
	Charge		TCO <sub>2</sub> Eq		2,19						
	Control				Expansion valve						
LW(A) Sound power level (according to EN14825)					56						
Sound pressure level (at 1 meter)	Nom.				41,1						
Power supply	Name/Phase/Frequency/Voltage			Hz/V	W1/3~/50 /400						
Current	Recommended fuses			A	16						



This product contains fluorinated greenhouse gases.

# Daikin Altherma 3 R MT F

Floor standing unit integrated with different temperature zones management

- › A combined stainless steel domestic hot water tank of 180 or 230L and heat pump for easy installation
- › Bi-zone allows temperature monitoring for 2 zones. Connect underfloor heating to radiators to optimise efficiency
- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Inclusion of all hydraulic components means no third party components are required
- › The unit's sleek design blends in with other household appliances



Efficiency data				ELVZ + ERRA	12S18E6V/9W + 08EV3	12S23E6V/9W + 08EV3	12S18E6V/9W + 10EV3	12S23E6V/9W + 10EV3	12S18E6V/9W + 12EV3	12S23E6V/9W + 12EV3		
	Space heating	Average climate water outlet 55 °C	General	SCOP	%	3,34			3,44			
				ηs (Seasonal space heating efficiency)		130	131	135				
		Seasonal space heating eff. class	A++									
	Average climate water outlet 35 °C	General	SCOP	%	4,69	4,71						
			ηs (Seasonal space heating efficiency)		184	186						
		Seasonal space heating eff. class		A+++								
	General	Declared load profile			L							
	Average climate	COP			dhw	2,72	2,96	2,72	2,96	2,72	2,96	
		ηwh (water heating efficiency)			%	117	126	117	126	117	126	
		Water heating energy efficiency class				A+						
Indoor Unit					ELVZ	12S18E6V/9W	12S23E6V/9W	12S18E6V/9W	12S23E6V/9W	12S18E6V/9W	12S23E6V/9W	
Casing	Colour					White + Black						
	Material					Precoated sheet metal						
Dimensions	Unit	HeightxWidthxDepth			mm	1,655 x 595 x 634	1,855 x 595 x 634	1,655 x 595 x 634	1,855 x 595 x 634	1,655 x 595 x 634	1,855 x 595 x 634	
Weight	Unit					kg	133	141	133	141	133	141
Tank	Water volume				l	180	230	180	230	180	230	
	Maximum water temperature				°C	70						
	Maximum water pressure				bar	10						
	Corrosion protection					Pickling						
Operation range	Heating	Ambient	Min.~Max.		°C	-25 ~ 25						
		Water side	Min.~Max.		°C	15 ~ 65						
	Domestic hot water	Ambient	Min.~Max.		°C	-25 ~ 35						
		Water side	Min.~Max.		°C	25 ~ 62						
Sound power level	Nom.					dBA	44					
Sound pressure level	Nom.					dBA	30					
Outdoor Unit					ERRA	08EV3	08EV3	10EV3	10EV3	12EV3	12EV3	
Dimensions	Unit	HeightxWidthxDepth			mm	1,003 x 1,270 x 533						
Weight	Unit					kg	107					
Compressor	Quantity					1						
	Type					Hermetically sealed swing compressor						
Operation range	Heating	Min.~Max.		°CDB	-25 ~ 25							
	Cooling	Min.~Max.		°CDB	10 ~ 43							
	Domestic hot water	Min.~Max.		°CDB	-25 ~ 35							
Refrigerant	Type					R-32						
	GWP					675						
	Charge					kg	3,25					
	Charge					TCO <sub>2</sub> Eq	2,19					
	Control					Expansion valve						
LW(A) Sound power level (according to EN14825)						54						
Sound pressure level (at 1 meter)						40,6						
Power supply	Name/Phase/Frequency/Voltage				Hz/V	V3/1~/50 /230						
Current	Recommended fuses				A	32						

This product contains fluorinated greenhouse gases.

## Floor standing unit with integrated ECH<sub>2</sub>O tank

The Daikin Altherma high temperature split integrated ECH<sub>2</sub>O is renowned for its ability to maximise renewable energy sources to provide the ultimate comfort in heating, domestic hot water and cooling

### Intelligent storage management

- › The unit is 'Smart Grid' ready to take advantage of low energy tariffs and efficiently store thermal energy for space heating and domestic hot water
- › Continuous heating during defrost mode and use of stored heat for space heating (500 L tank only)
- › Electronic management of both heat pump and ECH<sub>2</sub>O thermal store maximises energy efficiency, as well as convenient heating and domestic hot water
- › Achieves the highest standards for water sanitation
- › Uses more renewable energy with solar connection

### Innovative and high-quality tank

- › Lightweight plastic tank
- › No corrosion, anode, scale or lime deposits
- › Contains impact resistant polypropylene inner and outer walls filled with high-grade insulation foam to reduce heat losses to a minimum

### Combinable with other heat sources

- › The bivalent option allows heat from other sources such as oil, gas or pellet-fired boilers to be stored in the solar system, further lowering energy consumption

## ECH<sub>2</sub>O

Outdoor unit connection

Hydraulics

Controller display

Polypropylene tank



### Advanced user interface

#### The Daikin-Eye

The intuitive Daikin eye shows you in real time the status of your system. Blue is perfect! Should the eye turn red, an error has occurred.

### Quick to configure

Log in and you'll be able to completely configure the unit in less than 10 steps. You can even check if the unit is ready for use by running test cycles!

### Easy operation

The user interface works really fast thanks to its icon-based menus.

### Beautiful design

The interface was especially designed to be very intuitive. The high contrasted colour screen delivers stunning and practical visuals that really help you as installer or service engineer.



## ECH<sub>2</sub>O thermal store range: additional hot water comfort

Combine your indoor unit with a thermal store to achieve the ultimate comfort at home.

- › Fresh water principle: receive domestic hot water on demand while eliminating the risk of contamination and sedimentation
- › Optimal domestic hot water performance: the low temperature evolution enables high tapping performance
- › Fit for the future: possibility to integrate with renewable solar energy and other heat sources, e.g. fireplace
- › Lightweight and robust build of the unit combined with the cascade principle offers flexible installation options

Built for small and large homes, customers can choose between a pressureless and a pressurised hot water system.


### Pressureless (drain-back) solar system (ELSH\*, ELSX\*)

- › The solar collectors are only filled with water when sufficient heating is provided by the sun
- › The pumps in the control and pump unit switch on briefly and fill the collectors with storage tank water
- › After filling, water circulation is maintained by the remaining pump

### Pressurised solar system (ELSHB\*, ELSXB\*)


- › System is filled with heat transfer fluid with the correct amount of antifreeze to avoid freezing in winter
- › System is pressurised and sealed

**Monthly energy consumption of an average detached house**



**System diagram: Integrated solar unit**

- 1 Use of solar energy for domestic hot water and central heating
- 2 External heat pump unit
- 3 Solar thermal collectors
- 4 Solar pump station





# Daikin Altherma 3 R MT ECH<sub>2</sub>O

Floor standing air to water heat pump for **heating**, **cooling** and **hot water** with thermal solar support

- › Integrated solar unit, offering top comfort in heating and hot water
- › Maintenance-free tank: no corrosion, anode, scale or lime deposits, and no loss of water through safety valve
- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Maximum use of renewable energy: uses heat pump technology for heating and solar support for space heating and domestic hot water production
- › Fresh water principle: hygienic water, with no need for thermal legionella disinfection



Efficiency data				ELSX+ ERRA	12P30E + 08EW1	12P50E + 08EW1	12P30E + 10EW1	12P50E + 10EW1	12P30E + 10EW1	12P50E + 10EW1	
	Space heating	Average climate water outlet 55 °C	General	SCOP	3,47		3,48		3,48		
				ηs (Seasonal space heating efficiency)			136				
			Seasonal space heating eff. class			A++					
	Average climate water outlet 35 °C	General	SCOP	4,95				4,98			
			ηs (Seasonal space heating efficiency)	195				196			
			Seasonal space heating eff. class			A+++					
	Domestic hot water heating	General	Declared load profile		L	XL	L	XL	L	XL	
		Average climate	COP	dhw	2,83	3,29	2,83	3,29	2,83	3,29	
			ηwh (water heating efficiency)	%	119	136	119	136	119	136	
			Water heating energy efficiency class			A+					
Indoor Unit				ELSX	12P30E	12P50E	12P30E	12P50E	12P30E	12P50E	
Casing	Colour				Traffic white (RAL9016) / Traffic black (RAL9017)						
	Material				Impact resistant polypropylene						
Dimensions	Unit	HeightxWidthxDepth	mm	1,893 x 594 x 680	1,910 x 792 x 817	1,893 x 594 x 680	1,910 x 792 x 817	1,893 x 594 x 680	1,910 x 792 x 817		
Weight	Unit				76	91	76	91	76	91	
Tank	Water volume				294	477	294	477	294	477	
	Maximum water temperature				85						
Operation range	Heating	Ambient	Min.~Max.	°C	-25 ~25						
		Water side	Min.~Max.	°C	15 ~65						
	Domestic hot water	Ambient	Min.~Max.	°C	-25 ~35						
		Water side	Min.~Max.	°C	25 ~62						
Sound power level	Nom.				dBA	44,7					
Sound pressure level	Nom.				dBA	36,8					
Outdoor Unit				ERRA	08EW1	10EW1	12EW1				
Dimensions	Unit	HeightxWidthxDepth	mm	1,003 x 1,270 x 533							
Weight	Unit				kg	107					
Compressor	Quantity				1						
	Type				Hermetically sealed swing compressor						
Operation range	Heating	Min.~Max.	°CDB	-25 ~25							
	Domestic hot water	Min.~Max.	°CDB	-25 ~35							
Refrigerant	Type				R-32						
	GWP				675						
	Charge				kg	3,25					
	Charge				TCO <sub>2</sub> Eq	2,19					
	Control				Expansion valve						
LW(A) Sound power level (according to EN14825)				56							
Sound pressure level (at 1 meter)	Nom.				41,1						
Power supply	Name/Phase/Frequency/Voltage				Hz/V	W1/3~/50 /400					
Current	Recommended fuses				A	16					



This product contains fluorinated greenhouse gases.

# Daikin Altherma 3 R MT ECH<sub>2</sub>O

Floor standing air to water heat pump for **heating**, **cooling** and **hot water** with thermal solar support

- › Integrated solar unit, offering top comfort in heating and hot water
- › Maintenance-free tank: no corrosion, anode, scale or lime deposits, and no loss of water through safety valve
- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Maximum use of renewable energy: uses heat pump technology for heating and solar support for space heating and domestic hot water production
- › Fresh water principle: hygienic water, with no need for thermal legionella disinfection



Efficiency data				ELSX+ ERRA	12P30E + 08EV3	12P50E + 08EV3	12P30E + 10EV3	12P50E + 10EV3	12P30E + 12EV3	12P50E + 12EV3
	Space heating	Average climate water outlet 55 °C	General	SCOP	3,37		3,38		3,47	
				ηs (Seasonal space heating efficiency)	132		136			
				Seasonal space heating eff. class	A++					
	Average climate water outlet 35 °C	General	SCOP	4,79		4,82				
			ηs (Seasonal space heating efficiency)	188		190				
			Seasonal space heating eff. class	A+++						
	Domestic hot water heating	General	Declared load profile	L	XL	L	XL	L	XL	
		Average climate	COP	dhw	2,75	3,19	2,75	3,19	2,75	3,19
			ηwh (water heating efficiency)	%	116	132	116	132	116	132
			Water heating energy efficiency class	A+						
Indoor Unit				ELSX	12P30E	12P50E	12P30E	12P50E	12P30E	12P50E
Casing	Colour	Material			Traffic white (RAL9016) / Traffic black (RAL9017)					
					Impact resistant polypropylene					
Dimensions	Unit	HeightxWidthxDepth	mm	1,893 x 594 x 680	1,910 x 792 x 817	1,893 x 594 x 680	1,910 x 792 x 817	1,893 x 594 x 680	1,910 x 792 x 817	
Weight	Unit		kg	76	91	76	91	76	91	
Tank	Water volume		l	294	477	294	477	294	477	
	Maximum water temperature		°C	85						
Operation range	Heating	Ambient	Min.~Max.	°C	-25 ~25					
		Water side	Min.~Max.	°C	15 ~65					
	Domestic hot water	Ambient	Min.~Max.	°C	-25 ~35					
		Water side	Min.~Max.	°C	25 ~62					
Sound power level	Nom.		dBA	44,7						
Sound pressure level	Nom.		dBA	36,8						
Outdoor Unit				ERRA	08EV3	10EV3	12EV3			
Dimensions	Unit	HeightxWidthxDepth	mm	1,003 x 1,270 x 533						
Weight	Unit		kg	107						
Compressor	Quantity	Type			1					
	Hermetically sealed swing compressor									
Operation range	Heating	Min.~Max.	°CDB	-25 ~25						
	Domestic hot water	Min.~Max.	°CDB	-25 ~35						
Refrigerant	Type	Charge			R-32					
	GWP				675					
	kg				3,25					
	TCO <sub>2</sub> Eq				2,19					
	Control				Expansion valve					
LW(A) Sound power level (according to EN14825)				54						
Sound pressure level (at 1 meter)	Nom.				40,6					
Power supply	Name/Phase/Frequency/Voltage			Hz/V	V3/1~/50/230					
Current	Recommended fuses			A	32					



This product contains fluorinated greenhouse gases.

# Daikin Altherma 3 R MT ECH<sub>2</sub>O

Floor standing air-to-water heat pump for **heating and hot water** with thermal solar support

- › Integrated solar unit, offering top comfort in heating and hot water
- › Maintenance-free tank: no corrosion, anode, scale or lime deposits, and no loss of water through safety valve
- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Maximum use of renewable energy: uses heat pump technology for heating and solar support for space heating and domestic hot water production
- › Fresh water principle: hygienic water, with no need for thermal legionella disinfection



Efficiency data				ELSH + ERRA	12P30E + 08EW1	12P50E + 08EW1	12P30E + 10EW1	12P50E + 10EW1	12P30E + 12EW1	12P50E + 12EW1	
	Average climate water outlet 55 °C	General	SCOP	%	3,42		3,43		3,53		
			ηs (Seasonal space heating efficiency)	%	134				138		
		Seasonal space heating eff. class		A++							
	Average climate water outlet 35 °C	General	SCOP	%	4,81		4,84				
			ηs (Seasonal space heating efficiency)	%	190		191				
		Seasonal space heating eff. class		A+++							
	General	Declared load profile		L	XL	L	XL	L	XL		
	Average climate	COP	dhw	2,83	3,29	2,83	3,29	2,83	3,29		
		ηwh (water heating efficiency)	%	119	136	119	136	119	136		
		Water heating energy efficiency class		A+							
Indoor Unit				ELSH	12P30E	12P50E	12P30E	12P50E	12P30E	12P50E	
Casing	Colour	Traffic white (RAL9016) / Traffic black (RAL9017)									
	Material	Impact resistant polypropylene									
Dimensions	Unit	HeightxWidthxDepth	mm	1,893 x 594 x 680	1,910 x 792 x 817	1,893 x 594 x 680	1,910 x 792 x 817	1,893 x 594 x 680	1,910 x 792 x 817		
Weight	Unit		kg	76	91	76	91	76	91		
Tank	Water volume		l	294	477	294	477	294	477		
	Maximum water temperature		°C	85							
Operation range	Heating	Ambient	Min.~Max.	°C	-25 ~25						
		Water side	Min.~Max.	°C	15 ~ 65						
	Domestic hot water	Ambient	Min.~Max.	°C	-25 ~ 35						
		Water side	Min.~Max.	°C	25 ~ 62						
Sound power level	Nom.		dBA	44,7							
Sound pressure level	Nom.		dBA	36,8							
Outdoor Unit				ERRA	08EW1	10EW1	12EW1				
Dimensions	Unit	HeightxWidthxDepth	mm	1,003 x1,270 x533							
Weight	Unit		kg	107							
Compressor	Quantity			1							
	Type			Hermetically sealed swing compressor							
Operation range	Heating	Min.~Max.	°CDB	-25 ~25							
	Domestic hot water	Min.~Max.	°CDB	-25 ~35							
Refrigerant	Type			R-32							
	GWP			675							
	Charge		kg	3,25							
	Charge		TCO <sub>2</sub> Eq	2,19							
	Control			Expansion valve							
LW(A) Sound power level (according to EN14825)				56							
Sound pressure level (at 1 meter)	Nom.			41,1							
Power supply	Name/Phase/Frequency/Voltage			Hz/V	W1/3~/50 /400						
Current	Recommended fuses			A	16						

This product contains fluorinated greenhouse gases.





# Daikin Altherma 3 R MT ECH<sub>2</sub>O

Floor standing air-to-water heat pump for **heating and hot water** with thermal solar support

- › Integrated solar unit, offering top comfort in heating and hot water
- › Maintenance-free tank: no corrosion, anode, scale or lime deposits, and no loss of water through safety valve
- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Maximum use of renewable energy: uses heat pump technology for heating and solar support for space heating and domestic hot water production
- › Fresh water principle: hygienic water, with no need for thermal legionella disinfection



Efficiency data				ELSH + ERRA	12P30E + 08EV3	12P50E + 08EV3	12P30E + 10EV3	12P50E + 10EV3	12P30E + 12EV3	12P50E + 12EV3	
	Space heating	Average climate water outlet 55 °C	General	SCOP	%	130	3,44				
				ηs (Seasonal space heating efficiency)			131		135		
	Seasonal space heating eff. class	A++									
	Average climate water outlet 35 °C	General	SCOP	%	4,69	4,71			186		
ηs (Seasonal space heating efficiency)			184								
Seasonal space heating eff. class			A+++								
	General	Declared load profile			L	XL	L	XL	L	XL	
	Average	COP			2,75	3,19	2,75	3,19	2,75	3,19	
	climate	ηwh (water heating efficiency)			116	132	116	132	116	132	
	Water heating energy efficiency class			A+							
Indoor Unit				ELSH	12P30E	12P50E	12P30E	12P50E	12P30E	12P50E	
Casing	Colour				Traffic white (RAL9016) / Traffic black (RAL9017)						
	Material				Impact resistant polypropylene						
Dimensions	Unit	HeightxWidthxDepth		mm	1,893 x 594 x 680	1,910 x 792 x 817	1,893 x 594 x 680	1,910 x 792 x 817	1,893 x 594 x 680	1,910 x 792 x 817	
Weight	Unit				kg	76	91	76	91	76	91
Tank	Water volume			l	294	477	294	477	294	477	
	Maximum water temperature			°C	85						
Operation range	Heating	Ambient	Min.~Max.	°C	-25 ~25						
		Water side	Min.~Max.	°C	15 ~65						
	Domestic hot water	Ambient	Min.~Max.	°C	-25 ~35						
		Water side	Min.~Max.	°C	25 ~62						
Sound power level	Nom.				dBA	44,7					
Sound pressure level	Nom.				dBA	36,8					
Outdoor Unit				ERRA	08EV3		10EV3		12EV3		
Dimensions	Unit	HeightxWidthxDepth		mm	1,003 x 1,270 x 533						
Weight	Unit				kg	107					
Compressor	Quantity				1						
	Type				Hermetically sealed swing compressor						
Operation range	Heating	Min.~Max.		°CDB	-25 ~ 25						
	Domestic hot water	Min.~Max.		°CDB	-25 ~35						
Refrigerant	Type				R-32						
	GWP				675						
	Charge				kg	3,25					
	Charge				TCO <sub>2</sub> Eq	2,19					
	Control				Expansion valve						
LW(A) Sound power level (according to EN14825)					54						
Sound pressure level (at 1 meter)	Nom.				40,6						
Power supply	Name/Phase/Frequency/Voltage			Hz/V	V3/1~/50 /230						
Current	Recommended fuses			A	32						

This product contains fluorinated greenhouse gases.


# Wall mounted unit

## Why choose Daikin wall mounted unit?

The Daikin Altherma 3 split wall mounted unit offers heating and cooling with high flexibility for a quick and easy installation, with an optional connection to deliver domestic hot water.

### High flexibility for installation and domestic hot water connection

- › Inclusion of all hydraulic components means no third party components are required
- › PCB board and hydraulic components are located in the front for easy access
- › Compact dimensions allows for small installation space, as almost no side clearances are required
- › The unit's sleek design blends in with other household appliances
- › Combine with a stainless steel or ECH<sub>2</sub>O thermal store



## Flexibility in providing domestic hot water

If the end user requires hot water and installation height is limited, a separate stainless steel tank provides the required installation flexibility.

ECH<sub>2</sub>O thermal store range: additional hot water comfort

Combine your wall mounted unit with a thermal store for additional hot water comfort.

- › Fresh water principle: receive domestic hot water on demand while eliminating the risk of contamination and sedimentation
- › Optimal domestic hot water performance: with high tapping performance
- › Fit for future possibility to integrate with renewable solar energy and other heat sources, e.g. fireplace
- › Lightweight and robust build on the unit combined with cascade principle offers flexible installation options



## Flexibility in providing space heating

The wall mounted unit is the perfect choice in case the end user is looking for space heating or cooling while domestic hot water is provided by another system.

Example of installation with a stainless steel domestic hot water tank.

### Heating and cooling




# Daikin Altherma 3 R MT W

Wall mounted **heating only** air to water heat pump

- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Compact dimensions allows for small installation space, as almost no side clearances are required.
- › Combine with a stainless steel tank or ECH<sub>2</sub>O thermal store.
- › Inclusion of all hydraulic components means no third party components are required
- › The unit's sleek design blends in with other household appliances



Efficiency data				ELBH + ERRA	12E6V/9W + 08EW1	12E6V/9W + 08EV3	12E6V/9W + 10EW1	12E6V/9W + 10EV3	12E6V/9W + 12EW1	12E6V/9W + 12EV3
	Space heating	Average climate water outlet 55 °C	General	SCOP	3,42	3,42	3,42	3,42	3,42	3,42
				η <sub>sp</sub> (Seasonal space heating efficiency)	134	130	134	131	138	135
				Seasonal space heating eff. class	A++	A++	A++	A++	A++	A++
	Average climate water outlet 35 °C	General	SCOP	4,81	4,69	4,84	4,71	4,84	4,71	
			η <sub>sp</sub> (Seasonal space heating efficiency)	190	184	191	186	191	186	
			Seasonal space heating eff. class	A+++	A+++	A+++	A+++	A+++	A+++	
Indoor Unit				ELBH	12E6V	12E9W	12E6V	12E9W	12E6V	12E9W
Casing	Colour		White + Black							
	Material		Resin, sheet metal							
Dimensions	Unit	HeightxWidthxDepth		mm	840 x 440 x 390					
Weight	Unit			kg	48,5					
Operation range	Heating	Ambient	Min.~Max.	°C	-25 ~ 25					
		Water side	Min.~Max.	°C	15 ~ 65					
	Domestic hot water	Ambient	Min.~Max.	°C	-25 ~ 35					
		Water side	Min.~Max.	°C	25 ~ 62					
Sound power level	Nom.			dBA	44					
Sound pressure level	Nom.			dBA	30					
Outdoor Unit				ERRA	08EW1	08EV3	10EW1	10EV3	12EW1	12EV3
Dimensions	Unit	HeightxWidthxDepth		mm	1,003 x 1,270 x 533					
Weight	Unit			kg	107					
Compressor	Quantity		1							
	Type		Hermetically sealed swing compressor							
Operation range	Heating	Min.~Max.		°CDB	-25 ~ 25					
	Domestic hot water	Min.~Max.		°CDB	-25 ~ 35					
Refrigerant	Type		R-32							
	GWP		675							
	Charge		kg	3,25						
	Charge		TCO <sub>Eq</sub>	2,19						
	Control		Expansion valve							
LW(A) Sound power level (according to EN14825)					56	54	56	54	56	54
Sound pressure level Nom. (at 1 meter)					41,1	40,6	41,1	40,6	41,1	40,6
Power supply	Name/Phase/Frequency/Voltage			Hz/V	W1/3~/50 /400	V3/1~/50 /230	W1/3~/50 /400	V3/1~/50 /230	W1/3~/50 /400	V3/1~/50 /230
Current	Recommended fuses			A	16	32	16	32	16	32


This product contains fluorinated greenhouse gases.

# Daikin Altherma 3 R MT W

Wall mounted **reversible** air to water heat pump for heating and cooling

- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Compact dimensions allows for small installation space, as almost no side clearances are required.
- › Combine with a stainless steel tank or ECH<sub>2</sub>O thermal store.
- › Inclusion of all hydraulic components means no third party components are required
- › The unit's sleek design blends in with other household appliances



Efficiency data				ELBX + ERRA	12E6V/9W + 08EW1	12E6V/9W + 08EV3	12E6V/9W + 10EW1	12E6V/9W + 10EV3	12E6V/9W + 12EW1	12E6V/9W + 12EV3
	Space heating	Average climate water outlet 55 °C	General	SCOP	3,47	3,37	3,48	3,38	3,58	3,47
				ηs (Seasonal space heating efficiency)	136	132	136	132	140	136
				Seasonal space heating eff. class	A++					
	Average climate water outlet 35 °C	General	SCOP	4,95	4,79	4,98	4,82	4,98	4,82	
			ηs (Seasonal space heating efficiency)	195	188	196	190	196	190	
				Seasonal space heating eff. class	A+++					
Indoor Unit				ELBX	12E6V	12E9W	12E6V	12E9W	12E6V	12E9W
Casing	Colour				White + Black					
	Material				Resin, sheet metal					
Dimensions	Unit	HeightxWidthxD		mm	840 x 440 x 390					
Weight	Unit			kg	48,5					
Operation range	Heating	Ambient	Min.~Max.	°C	-25 ~25					
		Water side	Min.~Max.	°C	15 ~65					
	Domestic hot water	Ambient	Min.~Max.	°C	-25 ~35					
		Water side	Min.~Max.	°C	25 ~62					
Sound power level	Nom.			dB(A)	44					
Sound pressure level	Nom.			dB(A)	30					
Outdoor Unit				ERRA	08EW1	08EV3	10EW1	10EV3	12EW1	12EV3
Dimensions	Unit	HeightxWidthxD		mm	1,003 x 1,270 x 533					
Weight	Unit			kg	107					
Compressor	Quantity				1					
	Type				Hermetically sealed swing compressor					
Operation range	Heating	Min.~Max.	°CDB		-25 ~ 25					
	Domestic hot water	Min.~Max.	°CDB		-25 ~ 35					
Refrigerant	Type				R-32					
	GWP				675					
	Charge			kg	3,25					
	Charge			TCO <sub>Eq</sub>	2,19					
	Control				Expansion valve					
LW(A) Sound power level (according to EN14825)					56	54	56	54	56	54
Sound pressure level (at 1 meter)	Nom.				41,1	40,6	41,1	40,6	41,1	40,6
Power supply	Name/Phase/Frequency/Voltage			Hz/V	W1/3~/50/400	V3/1~/50/230	W1/3~/50/400	V3/1~/50/230	W1/3~/50/400	V3/1~/50/230
Current	Recommended fuses			A	16	32	16	32	16	32

This product contains fluorinated greenhouse gases.









# Thermal stores and tanks

## Hot water heating installation options

### Why choose a thermal store or domestic hot water tank?

Whether you only need hot water or you want to combine your hot water with solar systems, we offer you the best solutions to the highest levels of comfort, energy efficiency and reliability.



ECH<sub>2</sub>O thermal store



Stainless steel tank

### ☒ Domestic hot water tank

#### Stainless steel tanks

##### Comfort

- › Available in 150, 180, 200, 250 and 300 litres in stainless steel EKHWS(U)-D

##### Efficiency

- › High-quality insulation keeps heat loss to a minimum
- › Efficient temperature heating: from 10 °C to 50 °C in only 60 minutes
- › Available as an integrated solution or separate tank

##### Reliability

- › At necessary intervals, the unit can heat up water up to 60 °C to prevent the risk of bacteria growth



## The ECH<sub>2</sub>O thermal store range

### ECH<sub>2</sub>O thermal store: additional hot water comfort

Combine your monobloc with a thermal store to achieve the ultimate comfort at home.

- › Fresh water principle: receive domestic hot water on demand while eliminating the risk of contamination and sedimentation
- › Optimal domestic hot water performance: the low temperature evolution enables high tapping performance
- › Fit for the future: possibility to integrate with renewable solar energy and other heat sources, e.g. fireplace
- › Lightweight and robust build of the unit combined with the cascade principle offers flexible installation options


Built for small and large homes, customers can choose between a pressureless and a pressurised hot water system.

### Efficiency


- › Fit for the future: maximise renewable energy sources
- › Intelligent Heat Storage Management: ensures continuous heating during defrost mode, and uses stored heat for space heating
- › High-quality insulation keeps heat loss to a minimum

### Reliability

- › Maintenance-free tank: no corrosion, anode, scale or lime deposits, and no water loss through the safety valve



Drain-back solar system




Pressurised solar system

### Pressureless (drain-back) solar system


- › The solar collectors are only filled with water when sufficient heating is provided by the sun
- › The pumps in the control and pump unit switch on briefly and fill the collectors with storage tank water
- › After filling, water circulation is maintained by the remaining pump

### Pressurised solar system

- › System is filled with heat transfer fluid with the correct amount of antifreeze to avoid freezing in winter
- › System is pressurised and sealed



### Monthly energy consumption of an average detached house



# Thermal store

## Plastic domestic hot water tank with solar support

- › Tank designed for connection with pressurised thermal solar system
- › Tank designed for connection with drainback thermal solar system
- › Available in 300 and 500 liters
- › Large hot water storage tank to provide domestic hot water at any time
- › Heat loss is reduced to a minimum thanks to the high quality insulation
- › Space heating support possible (500 L tank only)



Accessory				EKHWP	300B	500B	300PB	500PB	
Casing	Colour				Traffic white (RAL9016) / Dark grey (RAL7011)				
	Material				Impact resistant polypropylene				
Dimensions	Unit	Width	mm	595	790	595	790		
		Depth	mm	615	790	615	790		
Weight	Unit	Empty	kg	58	82	58	89		
Tank	Water volume	l			294	477	294	477	
	Material				Polypropylen				
	Maximum water temperature	°C			85				
	Insulation	Heat loss	kWh/24h	1.5	1.7	1.5	1.7		
	Energy efficiency class				B				
	Standing heat loss	W			64	72	64	72	
	Storage volume	l			294	477	294	477	
	Heat exchanger	Domestic hot water	Quantity				1		
Tube material						Stainless steel (DIN 1.4404)			
Face area			m²	5,600	5,800	5,600	5,900		
Internal coil volume			l	27.1	28.1	27.1	28.1		
Operating pressure			bar	6					
Charging		Average specific thermal output	W/K	2,790	2,825	2,790	2,825		
		Quantity				1			
		Tube material				Stainless steel (DIN 1.4404)			
		Face area	m²	3	4	3	4		
		Internal coil volume	l	13	18	13	18		
Pressurised solar		Operating pressure	bar	3					
		Average specific thermal output	W/K	1,300	1,800	1,300	1,800		
		Average specific thermal output	W/K	-			390	840	
		Auxiliary solar heating	Tube material	-			Stainless steel (DIN 1.4404)	-	Stainless steel (DIN 1.4404)
			Face area	m²	-	1	-	1	
Internal coil volume			l	-	4	-	4		
Operating pressure	bar		-	3	-	3			
Average specific thermal output	W/K		-	280	-	280			



# Domestic hot water tank

## Stainless steel domestic hot water tank

- › Available in 150, 180, 200, 250 and 300 litres
- › Stainless steel domestic hot water tank



EKHWS(U)-D

Accessory			EKHSU/EKHS/EKHS-P		150D3V3	180D3V3	200D3V3	250D3V3	300D3V3	150D3V3	180D3V3	200D3V3	250D3V3	300D3V3	
Casing	Colour		Neutral white												
	Material		Epoxy coated steel / Epoxy-coated mild steel												
Tank	Water volume	l	145	174	192	242	292	145	174	192	242	292			
	Material		Stainless steel (EN 1.4521)												
	Maximum water temperature	°C	75												
	Insulation Heat loss	kWh/24h	1.1 (1)	1.2 (1)	1.3 (1)	1.4 (1)	1.6 (1)	1.1 (1)	1.2 (1)	1.3 (1)	1.4 (1)	1.6 (1)			
	Energy efficiency class		B												
Heat exchanger	Domestic hot water	Quantity	1												
		Tube material	Stainless steel (EN 1.4521)												
		Face area	m²	1.050	1.400	1.800			1.050	1.400	1.800				
		Internal coil volume	l	4.9	6.5	8.2			4.9	6.5	8.2				
		Operating pressure	bar	10											
	Booster heater	Capacity	kW	3											
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/230												
Weight	Unit	Empty	kg	45 - 45	50 - 50	53 - 53	58 - 58	63 - 63	45 - 45	50 - 50	53 - 53	58 - 58	63 - 63		
Tank-Weight	Standing Unit	S - Empty heat loss	W - kg	45 - 45	50 - 50	55 - 53	60 - 58	68 - 63	45 - 45	50 - 50	55 - 53	60 - 58	68 - 63		
	Storage Unit	V - Empty volume	l - kg	145 - 45	174 - 50	192 - 53	242 - 58	292 - 63	145 - 45	174 - 50	192 - 53	242 - 58	292 - 63		

(1) Heat loss according to EN12897

# Daikin Altherma HPC Floor standing model



The floor standing heat pump convector impresses with its low sound operations, and its slim design that received the RedDot Award 2020. Next to heating and cooling, the unit can also provide indoor air quality control.

## Why Indoor Air Quality Matters

Indoor Air Quality (IAQ) refers to the air quality in a building or structure, breathed in every day by the building's occupants.

When planning new residential buildings, schools, offices or light commercial buildings, many things must be considered. Besides structural factors, there are also the topics of heating, cooling and something often neglected: indoor air quality.


Did you know that the indoor air we breathe, whether at home, at the office, or in a hotel room could in fact be much more polluted than the air outside?

- › 90 % of our lives is spent indoors
- › Indoor air quality can be 2 to 5 times worse than outdoor air quality because of pollutants, such as pollen, bacteria, etc.



## How does Daikin Altherma HPC ensure a healthy and comfortable indoor air quality?

When a pollutant level of indoor air is reached, the IAQ sensor opens a damper, which allows fresh air to come in. The incoming fresh air is immediately heated or cooled (depending on the demand) by the heat pump convector. In this way the indoor air remains of good quality while comfort is ensured.






## Slim design



The floor standing Daikin Altherma HPC has a depth of only 135 mm that fits any house or apartment. Its optimised design was rewarded with the Reddot Design Award 2020.




## Fast and high capacity

The Daikin Altherma HPC combines the advantages of residential underfloor heating and radiators. It delivers high-capacity heating or cooling faster and can be set at ultra-low temperatures (35/30 °C regime).



## Discreet

As the unit reaches its set point, a continuous modulating fan gradually reduces its speed and creates less noise. For the wall mounted and concealed units, the sound pressure measures 25dB(A) at 1m when the fan is on low-speed setting. Even lower sound pressure in super-silent mode (night mode).



## Controls

Daikin offers a wide variety of controllers that are functional and have a great design.

### EKRTCTRL1



- > Built-in controller
- > Fully modulating
- > Multicolor display

### EKRTCTRL2



- > Built-in controller
- > 4 speed settings

### EKWHCTRL1



- > Wall controller
- > Fully modulating
- > In combination with EKWHCTRL0

### EKPCBO



- > Built-in controller
- > ON/OFF
- > In combination with external thermostats

### EKWHCTRL1A




- > Wall controller
- > Fully modulating
- > In combination with EKWHCTRL0
- > Includes indoor air quality sensor

# Wall-mounted model

Thanks to its slim design, our wall-mounted unit blends in with your interior discreetly while helping you save valuable floor space.

## Slim design

Daikin Altherma HPC is a compact unit made of a design metal casing including all valves.



## Controls

Choice of:

- › Fully modulating controller allowing for remote control of the unit.
- › Infrared remote controller and on-board touch panel.

### EKWHCTRL1




- › Wall controller
- › Fully modulating
- › For models FWXT-ABTV3(L)

### Infrared remote controller



- › Remote
- › Fully modulating
- › For models FWXT-ABTV3C(L)

## Compactness



### 1 Slim depth

The depth of 128 mm is an outstanding technical achievement that ensures a perfect fit in any home.

### 2 More space for valves

Ease of installation: the space for hydraulic valves is wide and easily accessible.


### 3 Modulated airflow

When there is less heating demand, the unit modulates its airflow to slow down the fan rate, and in the process, lowers the operational sound.



Forget about your heating or cooling installation altogether: our concealed model vanishes into the wall or ceiling for visual comfort while preserving its unique heating and cooling capabilities.

## Slim design



Blue dimensions are for the front cover.

## Controls

### EKWHCTRL1



- › Wall controller
- › Fully modulating
- › In combination with EKWHCTRL0

## Flexible installation

Daikin Altherma HPC can be installed in four different ways, allowing you to install it in almost all conditions. The unit can be positioned horizontally or vertically. For horizontal, in-ceiling installation, three different possibilities are offered:

- › Horizontal cover panel and vertical grille for air outlet
- › Horizontal intake grille and vertical grille for air outlet
- › Horizontal intake and outlet grilles











# Onecta App

Now available with voice control

The Onecta App is for those who live their life on the go and who want to manage their heating system from their smartphone.




## onecta

NEW


### Voice control

To provide users with even more comfort and ease, the Onecta App now offers voice control. This hands-free feature cuts down on clicks to manage units faster than ever before.


Cross-functional and multilingual, voice control pairs well with any smart device, including Google Assistant and Amazon Alexa.



Example of using the voice control via Google Assistant




Example of using the voice control via Amazon Alexa



## Schedule

Set up a programme outlining when the system should operate, and create up to six actions per day.


- ✓ Schedule room temperature and operation mode
- ✓ Enable holiday mode to save costs



## Control

Customise the system to fit your lifestyle and year-round comfort levels.

- ✓ Change room and domestic hot water temperature
- ✓ Turn on powerful mode to boost hot water production



## Monitor

Receive a thorough overview of how the system is performing and how much energy it consumes.

- ✓ Check the status of the heating system
- ✓ Access energy consumption graphs (day, week, month)

Function availability depends on the system type, configuration and operation mode.  
The app functionality is only available if both the Daikin system and the app have a reliable internet connection.



Scan the QR code to download the app now



# User-friendly wired remote controller with premium design

Madoka. The beauty of simplicity

Madoka



**Black**  
RAL 9005 (matt)  
BRC1HHDK



**White**  
RAL9003 (glossy)  
BRC1HHDW



**Silver**  
RAL 9006 (metallic)  
BRC1HHDS

## Madoka combines refinement and simplicity

- › Sleek and elegant design
- › Intuitive touch-button control
- › Three colours to match any interior
- › Compact: measures only 85 x 85 mm

## Easy update via Bluetooth

It is strongly recommended to make sure that the user interface is up to date. To update the software or check if updates are available, all you need is a mobile device and the Madoka Assistant app. The app is available on Google Play and in the App Store.



## Award-winning design

Madoka received an IF Design Award and Reddot Product Design Award for its innovative design. These awards represent two of the most prestigious and largest design competitions in the world.



reddot award 2018  
winner







# Stand By Me, a journey to customer satisfaction

It's time to relax. With your customer's new Daikin installation and Stand By Me service program, you can rest assured they are benefiting from the best comfort, energy efficiency, usability and service available on the market. Stand By Me eliminates your clients' worries and provides them with a free, extended warranty, quick follow-up from Daikin service providers, and additional warranties for specific parts.

## Get on board on our train to ultimate customer satisfaction

On our underground map you can discover all the tools we offer to Daikin installers to help them from the first point of contact with a new client, to the maintenance and repair after installation.



**HSN**  
PRO

### Heating Solutions Navigator

Provide the best fit solution for your customers homes

 Web portal

 Professionals



### Daikin e-Care

Access to registration, configuration and trouble shooting

 Mobile app

 Professionals



### Stand By Me

Manage your installation database and offer comfort and service to your customer

 Web portal

 Professionals



### Onecta App

End-user app to control the residential unit

 Mobile app

 Consumer

## Discover the new features

We keep investing in the support towards our installers. With your Daikin account, you have access to Stand By Me and the Heating Solutions Navigator online. Use the same account to access the Daikin e-Care app. The tools offer now new features, check it out!



### Heating Solutions Navigator

Newest functions:  
underfloor heating, Fan Coil  
selection tool and ventilation  
quotation tool



### Onecta App

Newest function:  
voice control thanks to Amazon  
Alexa or Google Assistant



### Stand By Me

Newest function:  
20 installer settings for remote  
monitoring (SBM Pro)




### Daikin e-Care

Newest function:  
20 installer settings to solve  
problems remotely


## Error notification and 20 installer settings for remote support through SBM Pro and e-care app

From the professional portal, installers can activate the remote monitoring allowing them to supervise your installation on multiple parameters, from their location. They will get an automatic notification in case there is something wrong with the installation. By changing certain settings they can improve your comfort immediately. Save time and get a better support, thanks to these new features.

- ☒ Space heating/cooling
- ☒ Main zone & Additional zone (LWT)
- ☒ Domestic hot water
- ☒ Room (RT)
- ☒ Installer – Error handling




Adjust a room setpoint remotely




Adjust the weather-dependent curve remotely

# All about the Heating Solutions Navigator

The Heating Solutions Navigator is a digital toolbox developed for Daikin professionals with the aim to assist in providing the best fit solution for your customers homes. With this tool you can configure your installation, create custom made piping & wiring diagrams, set the configuration on your installation and much more.





#### Heating Solutions Navigator

- Do the radiator test
- Fan-coil selection
- Simplified Heat load
- Room by Room heat load
- Commissioning assistant
- Equipment list
- Piping & wiring
- Solar
- Underfloor heating
- Pipe sizing
- Literature
- Economic viability study
- Configuration
- Commissioning

#### e-Care Mobile App

- Commissioning assistant
- Commissioning
- e-Doctor
- Spareparts ordering
- System status notifications

#### Stand By Me

- Configuration
- Commissioning
- Warranty extension
- System status notifications

#### Onecta App

- Warranty extension
- Maintenance
- Remote control
- Appointment scheduler



# Combination table and options

Combination table and options			H/O
			3 R MT
			ELVH12S18E6V
			ELVH12S18E9W
			ELVH12S23E6V
			ELVH12S23E9W
Type	Description	Material name	
Outdoor unit		ERRA08EV3/W1	ⓘ
		ERRA10EV3/W1	ⓘ
		ERRA12EV3/W1	ⓘ
Controller	Madoka wired room thermostat	BRC1HHDK/S/W	ⓘ
	Wireless room thermostats	EKRTRB	ⓘ
	Wired digital thermostat	EKRTWA	ⓘ
	WLAN module	BRP069A71	ⓘ
	LAN module	BRP069A62	ⓘ
	WLAN cartridge	BRP069A78	ⓘ (1)
	Wired digital thermostat	EKWCTRD1I1V3	ⓘ
	Wired analog thermostat	EKWCTRAN1V3	ⓘ
	Wired underfloor heating base station	EKWUFHTA1V3	ⓘ
	Universal centralized controller	EKCC8-W, DCOM-LT/IO, LT/MB	ⓘ
Domestic hot water	Stainless steel tank	EKHWS(P)(U)150D3V3	
		EKHWS(P)(U)180D3V3	
		EKHWS(P)(U)200D3V3	
		EKHWS(P)(U)250D3V3	
		EKHWS(P)(U)300D3V3	
	Polypropylene tank	EKHWP300B	
		EKHWP500B	
		EKHWP300PB	
		EKHWP500PB	
	Third party tank kit	EKHY3PART	
		EKHY3PART2	
Sensors	External sensor for EKRTRB room thermostat	EKRTETS	ⓘ
	High voltage smart grid relay kit	EKRELSG	ⓘ
	Remote indoor temperature sensor	KRCS01-1	ⓘ (6)
	Remote outdoor temperature sensor	EKRSCA1	ⓘ (6)
	Generic Bizone kit (PCB only)	EKMIKPOA	ⓘ
	Generic Bizone kit	EKMIKPHA	ⓘ
Other options	Digital I/O PCB	EKRPIHBA	ⓘ (7)
	Demand PCB	EKRPIAHT	ⓘ
	PC USB cable	EKPCCAB4	ⓘ
	Conversion kit H/O to reversible for floor standing	EKHVCONV4	ⓘ
	Conversion kit H/O to reversible for wall mounted	EKHBCONV	
	Booster heater kit	EKBH3SD	
ECH <sub>2</sub> O options	Inline BUH - connection kit	EKECBUCO2AF	
	Inline BUH - 3kW, for *3V (1N~, 230 V, 3 kW)	EKECBUAF3V	
	Inline BUH - 6kW, for *6V (1N~, 230 V, 6 kW)	EKECBUAF6V	
	Inline BUH - 9kW, for *9WN (3N~, 400 V, 9 kW)	EKECBUAF9W	
	Caleffi sludge and magnetite separator SAS1	156021	
	Biv Connector Kit	EKECBIVCO2AF	
	DB connector Kit	EKECDBCO2AF	
	Solar kit HT incl. pump station	EKSRRPS4A	
Daikin Home Controls	Room thermostat	EKRCTRD12BA	ⓘ
	Room thermostat 2	EKRCTRD13BA	ⓘ
	Room sensor	EKRSEND11BA	ⓘ
	Access point	EKRACPUR1PA	ⓘ
	Radiator thermostat	EKRRTVTR2BA	ⓘ
	Floor Heating Controller	EKRUFHT61V3	ⓘ
	Actuator	EKWCVATR1V3	ⓘ
	Basic IO Box	EKRSIBDI1V3	ⓘ
	Multi IO Box	EKRMIBEV1V3	ⓘ
Daikin Home Hub		EKRHH	ⓘ

(1) Included in accessory bag.

(2) Dedicated connection kit: EKEPRHLT3HX.

(3) Dedicated connection kit: ETBH: EKEPRHLT5H / ETBX: EKEPRHLT5X.

(4) EKHY3PART can be used if you have a tank in which you can insert the thermistor.

(5) EKHY3PART2 can be used if you have a tank in which you can't insert a thermistor.

(6) Only one sensor can be connected: indoor or outdoor.

(7) Additional relays to allow bivalent control in combination with external room thermostat are field supply.

(8) Only 1 Backup heater can be connected on one unit: 3 or 6\* or 9 kW (\*No 6T1-model applicable).

EKECBUCO2AF is needed to connect the backup heater to the main unit.

(9) Only bivalent models.

(10) Only needed for 300 models. 500 models do not need DB connector kit to install DB solar system.

(11) Models EKHWSU150DV3, EKHWSU180DV3, EKHWSU200DV3, EKHWSU250DV3 and EKHWS-U300DV3 are not available for the UK.

Floor standing integrated tank		Floor standing integrated ECH <sub>2</sub> O	Wall mounted	
Reversible	Bizone		H/O	Reversible
3 R MT	3 R MT	3 R MT	3 R MT	3 R MT
ELVX12S18E6V	ELVZ12S18E6V	ELSH(B)12P30E		
ELVX12S18E9W	ELVZ12S18E9W	ELSH(B)12P50E		
ELVX12S23E6V	ELVZ12S23E6V	ELSX(B)12P30E	ELBH12E6V	ELBX12E6V
ELVX12S23E9W	ELVZ12S23E9W	ELSX(B)12P50E	ELBH12E9W	ELBX12E9W
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
• (1)	• (1)	• (1)	• (1)	• (1)
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
			• (11)	• (11)
			• (11)	• (11)
			• (11)	• (11)
			• (11)	• (11)
			• (11)	• (11)
			• (11)	• (11)
			• (2)	• (2)
			• (3)	• (3)
			• (2)	• (2)
			• (3)	• (3)
			• (4)	• (4)
			• (5)	• (5)
•	•	•	•	•
•	•	•	•	•
• (6)	• (6)	• (6)	• (6)	• (6)
• (6)	• (6)	• (6)	• (6)	• (6)
•		•	•	•
•		•	•	•
• (7)	• (7)		• (7)	• (7)
•	•	•	•	•
•	•	•	•	•
	•			
			•	
		•		
		• (8)		
		• (8)		
		• (8)		
		•		
		• (9)		
		• (10)		
		•		
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•



**Daikin Europe N.V.** Naamloze Vennootschap Zandvoordestraat 300 · 8400 Oostende · Belgium · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · RPR Oostende (Publisher)

FSC

ECPEN23-767

07/23



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

Printed on non-chlorinated paper.