


CK

Monosplit

Cooling capacity 2,7 ÷ 5,2 kW
Heating capacity 2,8 ÷ 5,3 kW

- **Standard Wi-Fi module.**
- **Air Purifiers (Cold Plasma).**
- **Low cooling function: cooling operation with outdoor temperatures down to -15°C.**
- **Low heating function: heating operation with outdoor temperatures down to -20°C.**



DESCRIPTION

The monosplit air conditioners of the CK range are combined with CK_FS (Console) indoor units with an inverter fan unit, offering twin delivery for optimum air flow control and enhanced environmental comfort. The outdoor unit features a compressor with inverter technology, an electronic valve and electric heater to ensure proper winter operation and prevent ice formation on the coil.

FEATURES

Indoor unit

A **Console** indoor unit designed to be installed on indoor walls or floor installation.

- Every indoor unit comes with a **WLRC20** remote control and remote control holder.
- Fan with DC inverter technology.
- Regenerable air filter easy to remove and clean.
- Timer for programming switch-off and switch-on.
- Indoor unit front panel with LED display and indicator lights.
- 5-speed fan, to meet every possible need.
- **AUTO** function for a continuous speed variation.
- **Turbo** function to attain the desired temperature as quickly as possible.
- Function **sleep** night time Well-being program.
- A **x-fan**, prolonged ventilation function prevent the formation of mould.
- **Anti-freeze** function that allows you to keep an inside minimum temperature of 8°C in winter.
- A **iFeel** function for activating the ambient temperature probe inside the remote control, for improved comfort.

Outdoor unit

Monosplit air conditioner.

Reversible air/air heat pump with DC inverter technology.

- Fitted with a electrical anti-freeze heater (in unit base) to avoid the formation of ice and encourage the drainage of condensate during heating operation.

- Compressor and fan with DC inverter technology.
- Fitted with an electronic expansion valve.


Smart APP Ewpe

This system is fitted **standard** with a wi-fi module that can be used, along with the app for iOS and Android devices (available free on Apple Store and Google Play), to control the system remotely on your smartphone or tablet, or via Cloud with the aid of a wireless router connected to the Internet.



Air Purifiers (Cold Plasma)

Capable of reducing pollutants breaking down their molecules using electric discharges, causing the splitting of the water molecules in the air into positive and negative ions. These ions neutralise the molecules of the gaseous pollutants obtaining products that are normally present in clean air. The device can eliminate 90% of bacteria. The result is clean, ionised air that has no bad odours.



General features

- Operating mode: cooling, heating, dehumidification, automatic and fan only.
- Particularly quiet operation.
- Microprocessor control.
- Auto-restart function.
- Self-diagnosis function.
- Air filter easily removed and cleaned.
- Easy installation and maintenance.

ACCESSORIES

WRCA: Wired panel with liquid crystal display and soft-touch buttons. This accessory can be used to control not only the traditional system functions but also a weekly timer with a maximum of 8 daily time bands.



ACCESSORIES COMPATIBILITY

	CK261	CK361	CK501
WRCA	.	.	.

PERFORMANCE SPECIFICATIONS

Indoor units	CK261FS	CK361FS	CK501FS	
Outdoor units	CK261	CK361	CK501	
Nominal cooling performances				
Cooling capacity (1)	kW	2,70	3,50	5,20
Cooling input power (1)	kW	0,70	1,10	1,60
EER (2)	W/W	3,67	3,18	3,25
Minimum cooling performances				
Cooling capacity	kW	0,50	1,03	1,26
Cooling input power	kW	0,20	0,93	0,38
Maximum cooling performances				
Cooling capacity	kW	3,33	3,80	6,60
Cooling input power	kW	1,30	1,35	2,45
Cooling input current	A	3,5	4,8	7,1
Seasonal efficiency				
SEER	W/W	6,50	6,40	6,50
Efficiency energy class (3)		A++	A++	A++
Pdesignc	kW	2,7	3,5	5,2
Annual power consumption	kWh/annum	145	192	280
Nominal cooling performances				
Moisture removed	l/h	0,8	1,2	1,8
Nominal heating performances				
Heating capacity (4)	kW	2,80	3,75	5,33
Heating input power (4)	kW	0,74	1,00	1,55
COP (2)	W/W	3,76	3,75	3,55
Minimum heating performances				
Heating capacity	kW	0,50	1,25	1,12
Heating input power	kW	0,20	0,19	0,35
Maximum heating performances				
Heating capacity	kW	3,50	4,40	6,80
Heating input power	kW	1,40	1,60	2,50
Heating input current	A	3,4	4,3	6,7
Seasonal efficiency (temperate climate)				
SCOP		4,00	4,00	4,10
Efficiency energy class (3)		A+	A+	A+
Pdesignh	kW	2,7	3,5	5,0
Annual power consumption	kWh/annum	945	1225	1707

(1) Cooling (EN-14511 and EN-14825) ambient air temperature 27 °C D.B. / 19 °C W.B.; outside air temperature 35 °C; max speed; length of refrigerant lines 5 m.

(2) EER/COP in accordance with the Standard (EN-14511), only declared for the purposes of the tax deductions in force at the time of this publication.

(3) Data in accordance with Delegated Regulation (EU) No. 626/2011.

(4) Heating (EN-14511 and EN-14825) ambient air temperature 20 °C D.B.; outside air temperature 7 °C D.B. / 6 °C W.B.; max speed; length of refrigerant lines 5 m.

INDOOR UNIT

Indoor unit		CK261FS	CK361FS	CK501FS
Input power	W	30	30	30
Type of fan	Type	Inverter centrifuge	Inverter centrifuge	Inverter centrifuge
Air flow rate				
Turbo	m ³ /h	500	600	700
Maximum	m ³ /h	430	520	650
Average	m ³ /h	370	440	520
Minimum	m ³ /h	280	360	410
Sound power				
Turbo	db(A)	52,0	52,0	57,0
Maximum	db(A)	48,0	50,0	55,0
Average	db(A)	44,0	46,0	50,0
Minimum	db(A)	38,0	41,0	45,0
Sound pressure (1)				
Turbo	db(A)	40,0	42,0	47,0
Maximum	db(A)	36,0	40,0	45,0
Average	db(A)	32,0	63,0	40,0
Minimum	db(A)	26,0	31,0	35,0
Indoor unit				
Condensate Discharge Diameter	mm	17,0	17,0	17,0

(1) Sound pressure measured in semi anechoic chamber at a distance of 1,5 m from the source.

OUTDOOR UNIT

Outdoor unit		CK261	CK361	CK501
Type of fan	Type	Inverter axial	Inverter axial	Inverter axial
Air flow rate				
Maximum	m ³ /h	1600	1600	3200
Sound power				
Maximum	db(A)	62,0	62,0	65,0
Sound pressure (1)				
Maximum	db(A)	52,0	52,0	57,0
Compressor				
Type	type	DC inverter rotary	DC inverter rotary	DC inverter rotary
Refrigerant	type	R410A	R410A	R410A
Refrigerant charge	kg	0,9	1,0	1,3
Potential global heating	GWP	2088kgCO ₂ eq	2088kgCO ₂ eq	2088kgCO ₂ eq
Equivalent CO ₂	t	1,88	1,98	2,71
Outdoor unit				
Condensate Discharge Diameter	mm	16,0	16,0	16,0


(1) Sound pressure measured in semi anechoic chamber at a distance of 1,5 m from the source.

GENERAL DATA

Indoor unit		CK261FS	CK361FS	CK501FS
Outdoor unit		CK261	CK361	CK501
Electric data				
Rated power input (1)	kW	1,4	1,6	2,5
Rated current input (1)	A	5,9	5,9	10,9
Refrigeration Pipework				
Diameter of liquid refrigerant connections	mm (inch)	6,35 (1/4")	6,35 (1/4")	6,35 (1/4")
Diameter of refrigerant gas connections	mm (inch)	9,52 (3/8")	9,52 (3/8")	12,7 (1/2")
Maximum refrigerant tube length	m	15	20	25
Maximum refrigerant line level difference	m	10,0	10,0	10,0
Refrigerant to be added	g/m	20	20	20
Power supply				
Power supply		220-240V ~ 50Hz	220-240V ~ 50Hz	220-240V ~ 50Hz

(1) The rated power input (rated current input) is the maximum input electrical power (maximum current input) from the system, in accordance with the Standards EN-60335-1 and EN-60335-2-40.

DIMENSIONS AND WEIGHTS



Indoor unit		CK261FS	CK361FS	CK501FS
A	mm	700	700	700
B	mm	215	215	215
C	mm	600	600	600
D	mm	788	788	788
E	mm	283	283	283
F	mm	697	697	697
Net weight	kg	16	16	16
Weight for transport	kg	19	19	19

Outdoor unit		CK261	CK361	CK501
A	mm	776	776	955
B	mm	320	320	396
C	mm	540	540	700
D	mm	823	823	1029
E	mm	358	358	458
F	mm	595	595	750
Net weight	kg	31	32	46
Weight for transport	kg	34	34	51

Aermec reserves the right to make any modifications deemed necessary.
All data is subject to change without notice. Aermec does not assume responsibility or liability for errors or omissions.

Aermec S.p.A.
Via Roma, 996 - 37040 Bevilacqua (VR) - Italia
Tel. 0442633111 - Telefax 044293577
www.aermec.com